



Slide Stabilization with a 17-Meter Tall Reinforced Earth Fill: Lessons Learned



By Jose N. Gomez, PE, MSc
Principal Engineer
ECS Mid-Atlantic, LLC

Williamsburg, October 1, 2013




Presentation Content

- **Introduction**
- **Soil Profile and Temporal Support System**
- **Cause of the Earth Slide**
- **Rehabilitation Alternatives**
- **Reinforced Earth Fill Design Considerations**
- **Fill Properties**
- **Construction Experiences and Behavior**
- **Lessons Learned**



Introduction

Jose N. Gomez, PE, MSc
ECS Mid-Atlantic, LLC



Williamsburg, October 1, 2013

Geotechnical Minute....



Slide Location – Aerial View Within the City Financial Center



8,000 + VPD

Bldg:
100,000 SF Lot
1M SF Total
19 Stories
4 Bsmts (then 5)

Breaking News...

May 9, 1994

Tension Cracks




Slide Cross Section






Soil Profile and Temporal Support System

Jose N. Gomez, PE, MSc
ECS Mid-Atlantic, LLC




Williamsburg, October 1, 2013

Temporal Support System






Cause of the Earth Slide



Jose N. Gomez, PE, MSc
ECS Mid-Atlantic, LLC

Williamsburg, October 1, 2013

What Was Going On??



The Buzz:

A Water Pipe Broke...
Water Pressure Built Up... and
Then... Everything Slid Down..


The Truth:

Earth Moved.. And Then,
Water Pipe Broke...

Cause of the Earth Slide

Lateral Earth Pressure Diagrams

Flexible Walls




Lessons Learned-Lateral Earth Pressure

BIG Lessons Learned:

- **CALL Geotech Eng. to Make decisions Involving Soil Issues**
- **Complete/Additional Geotechnical Exploration**
- **Do not Assume Soil Profile because Everything is All Right...**
- **Verify Changes in Soil Conditions**



Rehabilitation Alternatives



Jose N. Gomez, PE, MSc
ECS Mid-Atlantic, LLC

Williamsburg, October 1, 2013



Rehabilitation Alternatives

Purposes:

- Fast Track (Traffic Problem – 8,000 VPD)
- Quick Design Turn Around
- Do Not Reduce Bldg Footprint !
- Safe
- Economical




Rehabilitation Alternatives




Excavation footprint taken by 2 : 17% or 40.1% of total bldg area

Final Design





Reinforced Earth Fill Design Considerations – Fill Properties




Jose N. Gomez, PE, MSc
ECS Mid-Atlantic, LLC


Williamsburg, October 1, 2013

Reinforced Earth Fill Design Considerations

- Internal Stability
 - Material Properties (Geotextiles and Fill)
 - Pullout
 - Tensile Overstress
 - Local
- External Stability
 - Bearing Capacity
 - Slope Stability (Rigid Block Sliding)



Internal Stability



After G. F. Sowers

- Presión de la tierra
 $p = K \delta Z$

- Empuje de Tierra
 $P = p \times \Delta H$

- Fuerza de Tensión
 (Geotextil)
 $F = 2L \gamma Z \tan \delta$

$$Le = \frac{K \Delta H (F.S)}{2 \tan \delta}$$

Lateral Earth Pressure



Earth Thrust

Tension Force

Equivalent Length

Failure Hypothesis

3D rather than a 2D Failure Mechanism




W Geotextile

NW Geotextile was
selected

Material Properties

Geosynthetics

Earth Fill



Fill Properties

Type : GC


PI : 16%

S200: 19%

UW_{dry} : 1.86 Tn/m³ (116 pcf)

w : 11.1%



Tensile Stress



External Stability

Stability Analysis Parameters

Material	γ (kN/m ³)	ϕ (o)	C (kN/m ²)
Reinforced Fill	21.9	35	0 – 200
Failure Surface	-	30	0 – 200






External Stability-Load Considerations

- 1

Initial Stability: Bottom Support; No Traffic
- 2

Intermediate Stability: Bottom Support; Traffic
- 3


Final Stability: Bottom/Top support; Traffic







Construction Experiences and Behavior

Jose N. Gomez, PE, MSc
ECS Mid-Atlantic, LLC



Williamsburg, October 1, 2013


Construction Stages



Reinforced Fill – Clayey Gravel



Compactors



95% Mod. Proctor
Thin Lifts




Bottom Corner





Removing Shotcrete



Intermediate Supports



Tallest Face





Geotextile and Geogrid

Tide Work Conditions-Tallest Face



Construction Stages




Few Meters Away From Top



Near To The Top



Instrumentation



PR Settlement Plates
BM Monuments

Making It Watertight




Works Never Stopped



After 25 Days of Ground Zero

Psychological Support




Lessons Learned-Design & Construction

- Geotechnical involvement must be continuous, from beginning to end
- If things are working, do not assume they will continue to do so: get the facts
- Working along limited spaces requires patience and sharp approach
- Do Not Forget To Drill Those Borings!!



Thank You ! !!



Jose N. Gomez, PE, MSc
ECS Mid-Atlantic, LLC

